

CLAIMS

1. (canceled) A blank for forming a lens included in a lens assembly mounted in the circular opening in the base, said blank including a button component with a lens section capable of being formed into a desired optical curvature and a concentric magnet mounting section formed thereon, a magnetic ring positioned around said magnet mounting section, and a cap positioned over said magnetic ring and stem, said cap including a lens section capable of being formed into a desired optical curvature and a body portion having a material thickness capable of having threads formed thereon .

2. (amended) A In situ adjustable intraocular insert functioning as an artificial lens for insertion into the eye comprising:

 a base, said base comprising an outer annular body and having an inner wall defining an opening, the inner wall of said base comprising a threaded inner wall defining a circular opening;

 a lens assembly mounted in the circular opening in the base, said lens assembly including a button component, said bottom component having a front optical lens section and a concentric stem extending rearwardly therefrom, said concentric stem having a diameter less than the diameter of the front optical lens section, a ring means adapted for insertion onto an adherence with the concentric stem, a cap provided for positioning over said ring means and stem and aligning with the front optical lens section when assembled, said cap being adhered to the button component when assembled;

 a front optical lens section capable of being machined to the desired optical curvature so as to meet the desired dioptric power of the lens when implanted;

 said cap having an outer surface, and said outer surface of the cap being threaded to create external threads thereon, whereby the assembled lens can be threaded into the base for surgical implanting into the eye of a patient, and be adjusted in situ in the eye after its application.

3. (previously presented) The in situ adjustable intraocular insert of claim 2 wherein said base, button component, and cap are formed from PMMA.
4. (previously presented) The in situ adjustable intraocular insert of claim 3 wherein said ring means is a magnetic ring.
5. (previously presented) The in situ adjustable intraocular insert of claim 4 wherein said magnetic ring is formed from samarium cobalt.
6. (previously presented) The in situ adjustable intraocular insert of claim 2 wherein said threaded surface of the lens includes a lead thread having a radius less than a radius of said thread inner wall surface of the base to facilitate the introduction of the lens into said base.
7. (previously presented) The in situ adjustable intraocular insert of claim 4 wherein said magnet comprises equally spaced segments of magnetic material provided within the ring means.
8. (previously presented) The in situ adjustable intraocular insert of claim 2 wherein said lens is bi-convex.
9. (previously presented) The in situ adjustable intraocular insert of claim 2 wherein said front optical lens section has a convex surface on one surface, and is planer on the opposite surface.
10. (previously presented) The in situ adjustable intraocular insert of claim 2 wherein said artificial lens is provided for insertion into one of the lens capsule, ciliary sulcus, or anterior chamber of the eye, and wherein said base comprising a compressible and resilient outer annular body design to fit within the lens capsule or other portions of the eye.
11. (previously presented) The in situ adjustable intraocular insert of claim 2 wherein said artificial lens includes at least one curvilinear haptic on an outer edge thereof for securing the base annulus within the lens capsule of the eye.
12. (previously presented) The adjustable intraocular insert of claim 2 wherein an insert has a thickness of less than 100-thousandth inch (0.100).
13. (new) A blank for forming an ophthalmic lens, including a lens assembly, said lens assembly, having a front optical lens assembly and said front optical lens assembly having a button section, a concentric stem integrally

formed on and extending from the button section, said concentric stem having a fixed height, similar to the height of the button section, a magnetic ring, said magnetic ring having the same height as said concentric stem and provided for snugly seating onto said concentric stem so that the stem and magnetic ring have the same height when fixed together, a cap, said cap having a body with a bore formed therein, said stem and fixed ring provided for tightly fitting within said cap bore when the cap and front optical lens assembly are secured together therein the cap contacts the button of said lens assembly when secured together, said cap and button have sufficient height and of a material thickness capable of having a series of threads formed thereon, whereby the front optical lens assembly and the cap can be machined to the desired optical curvature to achieve the required dioptric power after assembly.